



Model	CC 200	CC 300	CC 340	CC 420	CC 550	CC 650	CC 900	CC 1200
<b>Nominal capacity t/h</b>	50	100	200	250	400	600	1000	1300
<b>Maximal capacity t/h</b>	75	150	250	300	600	800	1300	1700
<b>Max. length m.</b>								
<b>Standard</b>	60	60	60	60	60	60	60	60
<b>Optional</b>	80	80	80	80	80	80	80	80
<b>Case dimension mm.</b>								
<b>Width</b>	185	300	340	415	555	650	900	1200
<b>Height</b>	323	443	565	565	690	870	930	930
<b>Netto height</b>	190	310	410	410	515	720	740	740
<b>Net section m<sup>2</sup></b>	0,035	0,093	0,139	0,170	0,286	0,468	0,666	0,888
<b>Thickness mm.</b>								
<b>Drive/Tension station</b>	2,5+2,5	3+3	3+3	3+4	4+4	4+4	4+4	4+4
<b>Bottom</b>	3	3	3	4	4	4	4	4
<b>Wall</b>	2,5	3	3	4	4	4	4	4
<b>Roof</b>	1,5	1,5	1,5	2	2	2	2	2,5
<b>Chain Din 8167</b>								
<b>Standard type</b>	M56	M112	M160	M160	M224	2xM224	2xM315	3xM315
<b>Breaking load N</b>	56.000	112.000	160.000	160.000	224.000	448.000	630.000	945.000
<b>Optional chain type</b>	M80	M160	M224	M224	M315	2xM315	-	-
<b>Breaking load N</b>	80.000	160.000	224.000	224.000	315.000	630.000	-	-
<b>Sprocket</b>	Z8	Z8	Z8	Z8	Z10	Z12	Z12	Z12
<b>Shaft diameter mm.</b>								
<b>Drive</b>	60	80	100	110	120	140	160	180
<b>Tension</b>	40	50	60	60	70	80	80	90
<b>Material</b>								
<b>Casing</b>	Pre-galvanized steel S235 Z450 Pre-galvanized steel S235 Z600 Stainless steel AISI430 Food grade painted steel S235							
<b>Chain</b>	C45							
<b>Sprocket</b>	16 MnCr 5							
<b>Shaft</b>	42 CrMo 4							
<b>Weight kg</b>								
<b>Drive station without motor</b>	162	300	340	500	700	1196	1500	1790
<b>Tension station</b>	94	116	205	233	450	668	905	1060
<b>Casing km/m</b>	39	69	86	112	160	260	370	470

The data reported in this table are informative.